



EVDC-150 (NA) 2nd generation Specifications

Accelerating mass adoption of electric vehicles by delivering sustainable fast charging solutions that can be deployed anywhere



EVDC-150 (NA) 2nd generation

150kW DC Fast Charger

FEATURES

- True simultaneous charging charge two cars at the same time
- Future-proof design with 1000 V max output
- Driver friendly with a 10" LCD touchscreen and simple to use interface
- CHAdeMO, CCS1 and NACS charging configurations
- Ethernet, 4G and Wi-Fi network connectivity
- OCPP 1.6 and ISO 15118 compliant
- Start modes include plug-n-play, RFID card, OCPP and optional POS
- IP54 rated enclosure ideal for a wide range of locations and conditions



SPECIFICATIONS		SPECIFICATIONS CONT	
Connectors	CHAdeMO + CCS1 NACS + CCS1 CCS1 + CCS1	Start-up Mode	Automatic charging / RFID card / OCPP
		POS (Credit Card Reader)	Optional (enabling card payments)
Output Power	150 kW (can charge two cars simultaneously one at 60 kW and one at 90 kW))	LCD Display	10 inch touchscreen
		Protection	Over / under voltage protection, overload protection, short circuit protection, over / under temperature protection, surge protection, communication failure
Output Voltage	300 - 1000 V		
Output Max Current	300 A (0 - 300 A variable range)	IP rating	IP54
Supply Input	480 Vac	Emergency Stop Button	Yes
Supply Frequency	60 Hz	Cooling Method	Forced air cooling
Input Current	184 A (@ 480 Vac)	Operating Temperature	-4°F (-20°C) to 122°F (50°C)
Grounding Detection	30 mA	Operating Humidity	5%-95% without condensation
Efficiency	≥96% (50%-100% load)	Dimensions (W x D x H)	35.4 x 22.4 x 63.0 (900 x 570 x 1600) inch (mm)
Power Factor	≥0.99		
Harmonic Current	<5%	Weight	~347 kg (765 lbs)
Ripple Voltage	1%	Certification	CE, IEC 61851, ISO 15118
Network Connectivity	Ethernet / 4G / Wi-Fi	MTBF	100,000 hours
Communication Protocol	OCPP 1.6	Warranty	2 years as standard
Charging Cable Length	5 m (16.4 ft)		



EVESCO (PART OF POWER SONIC CORP.) NA, LATAM & APAC 365 Cabela Dr Suite 300, Reno, Nevada 89439 USA

T: +1 775 824 6500

Smispol 4, 3861 RS, Nijkerk The Netherlands T: +31 33 7410 700