



## EVDC-360 (NA) Specifications

Accelerating mass adoption of electric vehicles by delivering sustainable fast charging solutions that can be deployed anywhere



## **EVDC-360 (NA)**

360kW DC Fast Charger

## **FEATURES**

- Utilizing the latest in DC fast charging and liquid cooling technology
- Future-proof design with 1000 V max output
- Driver friendly with a 10" LCD touchscreen and simple to use interface
- CHAdeMO, CCS1 and NACS charging configurations
- · Ethernet, 4G and Wi-Fi network connectivity
- OCPP 1.6 and ISO 15118 compliant
- Start modes include plug-n-play, RFID card, OCPP and optional POS
- IP54 rated enclosure ideal for a wide range of locations and conditions



SPECIFICATIONS		SPECIFICATIONS CONT	
Connectors	CHAdeMO + CCS1 NACS + CCS1 CCS1 + CCS1	Start-up Mode	Automatic charging / RFID card / OCPP
		POS (Credit Card Reader)	Optional (enabling card payments)
Output Power	Charge one EV with up to 360 kW or two EVs at the same time up to 180 kW each)	LCD Display	10 inch touchscreen
		Protection	Over / under voltage protection, overload protection, short circuit protection, over / under temperature protection, surge protection, communication failure
Output Voltage	300 - 1000 V		
Output Max Current	400 A (0 - 400 A variable range)	IP rating	IP54
Supply Input	480 Vac	Emergency Stop Button	Yes
Supply Frequency	60 Hz	Cooling Method	Liquid cooling
Input Current	442 A (@ 480 Vac)	Operating Temperature	-4°F (-20°C) to 122°F (50°C)
<b>Grounding Detection</b>	30 mA	Operating Humidity	5%-95% without condensation
Efficiency	≥96% (50%-100% load)	Dimensions (W x D x H)	37.4 x 30.7 x 89.8 (950 x 780 x 2280) inch (mm)
Power Factor	≥0.99		
Harmonic Current	<5%	Weight	~718 kg (1583 lbs)
Ripple Voltage	1%	Certification	CE, IEC 61851, ISO 15118
Network Connectivity	Ethernet / 4G / Wi-Fi	MTBF	100,000 hours
Communication Protocol	OCPP 1.6	Warranty	2 years as standard
Charging Cable Length	5 m (16.4 ft)		



EVESCO (PART OF POWER SONIC CORP.) NA, LATAM & APAC 365 Cabela Dr Suite 300, Reno, Nevada 89439 USA

T: +1 775 824 6500

Smispol 4, 3861 RS,
Nijkerk
The Netherlands
T: +31 33 7410 700