



EVAC-9S IP66 (NA) Specifications

Accelerating mass adoption of electric vehicles by delivering sustainable EV charging solutions that can be deployed anywhere



EVAC-9S IP66 (NA)

Level 2 Charging Station with Media Screen


FEATURES

- Share customized content applicable to your venue with a 55 inch media display
- 9.6 kW / 40 A output
- SAE J1772 Type 1 dual charging cables
- Ethernet, 4G and Wi-Fi network connectivity
- IP66 rated design ideal for outdoor installation
- AG coated tempered glass screen, maintenance free
- Android OS media player
- OCPP 1.6J compliant
- Start modes include plug-and-play and RFID card



SPECIFICATIONS	
Connector Type	SAE J1772 Type 1
Output Power	9.6 kW
Output AC Current	40 A
Supply Input	208 / 240 VAC single phase (+/- 10%)
Supply Frequency	60 Hz
Network Connection	Ethernet, 4G and Wi-Fi
Communication Protocol	OCPP1.6J
Operating Temperature	-4°F (-20°C) to 113°F (45°C)
Charger Display	Small LCD screen and LED indicator
Operating Environment	Outdoor use
IP Rating	IP66
Charge Cable	Dual tethered type 1
Dimensions (W x H x D) inch (mm)	35.24 x 78.74 x 8.66 (895 x 2000 x 220)
Media Player Operating System	Android 7.1 OS
Media Player Input	USB 2.0

SPECIFICATIONS	
Media Screen Size	55 inch LCD
Resolution	1920 x 1080
Aspect Ratio	16:9
Brightness	2500 nits
Backlight Adjustment	Automatic (ambient light sensor)
Backlight Configuration	Direct LED
Enclosue Material	Galvanized steel, aluminum, zinc powder coating and fine grain powder coating
Glass	AG coating tempered glass, back painted pantone black C



J1772 TYPE 1



EVESCO (PART OF POWER SONIC CORP.)
NA, LATAM & APAC
365 Cabela Dr Suite 300,
Reno, Nevada 89439

T: +1 775 824 6500

Nijkerk
The Netherlands
T: +31 33 7410 700