

EVDS-CCS1/CCS1-33-BA (NA)

Distributed Charging

BABA-Compliant Distributed DC Fast Charging



Performance Specifications

| DC (Battery) Specifications   |                     |
|-------------------------------|---------------------|
| Battery Chemistry             | N/A                 |
| Stored Energy                 | N/A                 |
| Voltage                       | N/A                 |
| Battery Voltage Range         | N/A                 |
| DC Charge / Discharge Current | N/A                 |
| Supply Input                  | N/A                 |
| Frequency                     | N/A                 |
| Power Factor                  | N/A                 |
| Network Connectivity          | Ethernet, 4G, Wi-Fi |
| Communication Interface       | N/A                 |
| Cooling Method                | Forced air cooling  |

AC (PCS) Specifications

|                    |     |
|--------------------|-----|
| Rated Power        | N/A |
| Max. AC Power      | N/A |
| AC Rated Voltage   | N/A |
| Grid Voltage Range | N/A |
| AC Rated Current   | N/A |
| THDI               | N/A |

General Specifications

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| Cycle Life               | N/A                                                                                  |
| IP Rating                | IP55                                                                                 |
| Operating Temperature    | -13°F (-25°C) to 122°F (50°C)                                                        |
| Operating Humidity       | 5% - 95% without condensation                                                        |
| Fire Fighting System     | N/A                                                                                  |
| Gas Detection / Release  | N/A                                                                                  |
| Energy Management System | N/A                                                                                  |
| Weight                   | 485.0 lbs (220.0 kg)                                                                 |
| Dimensions               | <b>L:</b> 29.5in, 750.0mm<br><b>W:</b> 17.7in, 450.0mm<br><b>H:</b> 82.7in, 2100.0mm |
| Warranty                 | 3 years as standard                                                                  |



## EVDS-CCS1/CCS1-33-BA (NA)

# Distributed Charging BABA-Compliant Distributed DC Fast Charging



## Features

BABA-compliant distributed DC fast charging systems for large-scale fleet and depot deployments.

## Model Variations Available

## Approvals

Ask your Power-Sonic representative about additional certifications and approvals.

## For Further Information

Please refer to our website, **[www.power-sonic.com](http://www.power-sonic.com)**, for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.



To ensure safe and efficient operation always refer to the latest edition of our Technical Manual, as published on our website. © 2026, Power-Sonic Corporation. All rights reserved. All trademarks are the property of their respective owners. All data subject to change without notice. E&O.

Updated 6/26/2026 11:39 AM

Version 1.0