

PDC-62240- GC2

Deep Cycle AGM PDC Series - Deep Cycle AGM

Deep cycle AGM batteries engineered for long runtimes and repeated cycling. Rugged plate design and absorbent glass mat separators deliver dependable performance in applications such as mobility, marine, and renewables.

Performance Specs

Nominal Voltage 6.0 Volts, (3.0 cells)

Nominal Capacity

20-hr. (5.78A to 5.4 Volts)	224.0Ah
10-hr. (21.0A to 5.4 Volts)	210.0Ah
5-hr. (38.4A to 5.1 Volts)	192.0Ah
1-hr. (A to 4.8 Volts)	Ah

Approximate Weight 67.3lbs, (30.5kg)

Dimensions
+/- 0.08 in. (+/- 2mm) for length, width, and height dimensions

L: 10.24in, 260.0mm
W: 7.09in, 180.0mm
H: 9.96in, 253.0mm
TH: in, mm

Internal Resistance (approx.) mΩ mΩ

Max Short Circuit Discharge Current A

Operating Temperature Range
Charge 32°F (0°C) to 104°F (40°C)
Discharge -4°F (-20°C) to 131°F (55°C)

Case ABS Plastic Rated to UL94:HB


Recommended Power-Sonic Charger

Configuration Options

- PDC-62240-GC2 M8


Available Terminals (mm)

**T11 THREADED INSERT
- 8mm STUD**




Graphs


Capacity Retention SLA




PDC Cycle Life



SLA Charging



SLA Discharge Rates



Constant Current

Voltage	OverTime	30min	1h	1.5h	2h	3h	4h	5h	8h	10h	20h
1.60V/cell		219.62	133.0	96.32	81.15	59.86	46.7	40.31	26.88	21.7	11.58
1.67V/cell		216.46	131.1	95.06	79.88	59.33	46.3	39.89	26.45	21.5	11.45
1.70V/cell		213.3	129.2	93.58	78.83	58.81	45.7	39.03	26.24	21.3	11.3
1.75V/cell		209.08	126.67	91.9	77.14	57.7	44.8	38.4	25.81	21.0	11.2
1.80V/cell		204.87	120.77	87.26	73.35	56.49	44.0	37.75	25.6	20.8	11.09
1.85V/cell		188.22	116.56	84.52	71.03	52.06	41.2	35.83	24.32	19.7	10.71

Constant Power

Voltage	OverTime	30min	1h	1.5h	2h	3h	4h	5h	8h	10h	20h
1.60V/cell		407.25	253.23	184.53	155.95	114.57	90.45	78.29	52.69	42.45	22.83
1.67V/cell		405.55	251.31	183.04	154.67	114.13	89.81	77.44	52.05	42.01	22.61
1.70V/cell		402.77	249.17	181.33	152.96	113.48	88.75	76.16	51.63	41.59	22.4
1.75V/cell		398.08	245.55	178.56	150.61	111.76	87.68	75.09	50.77	41.17	22.19
1.80V/cell		393.17	235.09	170.67	143.79	109.83	86.4	74.03	50.56	40.94	21.97
1.85V/cell		363.95	228.27	165.76	139.73	101.51	81.07	70.83	48.21	39.01	21.33



Charging

Cycle Applications: Apply constant voltage charge at 2.35VPC – 2.45VPC (14.1 to 14.7 volts for 12V Monobloc) at 20°C. The initial charging current should be set at less than C/5 Amps. Switch to float charge when the current falls to a 3% capacity rate to avoid overcharging. Stand-By or "Float" Service: Apply constant voltage charge of 2.25VPC – 2.30VPC (13.5 to 13.8 volts for 12V Monobloc) at 20°C. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition. Temperature Compensation: Charging voltage for both cyclic and stand-by applications should be regulated in relation to ambient temperature. As temperature rises, charging voltage should be reduced to prevent overcharge and increased as the temperature falls to avoid undercharge. For further charging information, including temperature compensation factors, see the Power-Sonic Technical Manual.

Engineering Drawing

For Further Information

Please refer to our website, www.power-sonic.com, for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.

Approvals



CE marking confirms a product meets EU safety, health, and environmental protection standards for battery and energy systems.



Conflict-free mineral certification ensuring ethical sourcing and transparent supply chain for responsible production.



Extended mineral reporting meets global supply chain transparency standards for responsible and ethical sourcing practices.



IEC 60896 standard ensures stationary lead-acid batteries meet safety, performance, and float charge application requirements.



ISO 9001:2015 certification ensures consistent quality management and manufacturing standards for energy storage products.



PFAS-free certification verifying environmentally responsible manufacturing of batteries and energy storage technologies.



California Proposition 65 compliant, providing consumer safety through reduced chemical exposure in battery manufacturing.



REACH compliant with EU chemical safety standards ensuring restricted substances are controlled in all battery components.



RoHS compliance ensures restriction of hazardous substances in electrical, electronic, and battery-powered products.



Sealed lead-acid batteries classified UN2800 non-spillable, certified safe for air, sea, and ground transport worldwide.



SVHC compliant with EU REACH regulations for Substances of Very High Concern used in electrical and energy storage products.



U.S. EPA TSCA compliance ensures toxic substances are regulated for safe manufacturing of batteries and electronic components.



UL 1989 certified for valve-regulated and vented lead-acid batteries used in UPS, emergency, and backup power applications.

