

PG-12V12

Long Life AGM PG Series - Long Life

















Long life AGM batteries engineered for maximum reliability, extended float life, and reduced replacement costs. Advanced plate design and premium materials provide dependable backup power for security, emergency lighting, and critical standby systems.

Configuration Options

• PG-12V12 F2

Performance Specs

Nominal Voltage 12.0 Volts, (6.0 cells)

Nominal Capacity

20-hr. 11.2Ah (0.6A to 10.5 Volts) 12.0Ah 10-hr. 11.2Ah (1.12A to 10.5 Volts) 11.2Ah 5-hr. 10.35Ah (2.07A to 10.2 Volts) 10.35Ah 1-hr. 7.8Ah (7.8A to 9.6 Volts) 7.8Ah

Approximate Weight 8.53lbs, (3.87kg) **VDS** Weight lbs, (kg)

L: 5.94in, 151.0mm **Dimensions** W: 3.86in, 98.0mm +/- 0.08 in. (+/- 2mm) for length, H: 3.74in. 95.0mm width, and height dimensions TH: 3.98in, 101.0mm

Internal Resistance (approx.) $m\Omega$ $14.0 m\Omega$ 336.0A **Max Short Circuit Discharge Current**

Operating Temperature

Range

-4°F (-20°C) to 104°F (40°C) Charge 5°F (-15°C) to 122°F (50°C) Discharge

Case ABS (UL94 HB or V-0 optional)

Recommended Power-Sonic Charger PSC-121000ACX

Phone (US): (775) 825-6500

www.power-sonic.com

Phone (EMEA): +31 33 7410 700 Email (US): Sales@Power-Sonic.com

Email (EMEA): SalesEMEA@Power-Sonic.com

Available Terminals (mm)







Graphs

Capacity Retention SLA

CAPACITY RETENTION




PS Cycle Life




SLA Charging

CHARGING CHARACTERISTICS @ C/5 AND 25°C



SLA Float Life 10YR

FLOAT LIFE VS. TEMPERATURE



Constant Current

VoltageOverTime	5min	10min	15min	20min	30min	45min	1h	1.5h	2h	3h	4h	5h	6h	8h	10h	20h
1.60V/cell	49.6	31.9	23.5	18.6	13.5	9.6	7.8	5.7	4.45	3.16	2.5	2.12	1.81	1.42	1.16	0.616
1.65V/cell	47.2	30.9	22.9	18.2	13.2	9.5	7.6	5.6	4.38	3.12	2.47	2.1	1.8	1.4	1.14	0.612
1.67V/cell	46.8	30.6	22.7	18.1	13.1	9.4	7.6	5.6	4.36	3.1	2.46	2.09	1.79	1.4	1.14	0.61
1.70V/cell	45.2	29.8	22.1	17.7	12.9	9.3	7.5	5.5	4.32	3.07	2.44	2.07	1.77	1.39	1.14	0.605
1.75V/cell	43.2	28.6	21.4	17.2	12.6	9.1	7.4	5.4	4.25	3.03	2.4	2.04	1.75	1.38	1.12	0.6
1.80V/cell	41.0	27.5	20.7	16.7	12.2	8.9	7.2	5.3	4.18	2.98	2.37	2.02	1.73	1.36	1.11	0.593
1.85V/cell	38.1	26.0	19.7	16.1	11.9	8.6	7.0	5.2	4.1	2.93	2.34	1.99	1.7	1.34	1.1	0.587

Constant Power

VoltageOverTime	5min	10min	15min	20min	30min	45min	1 h	1.5h	2h	3h	4h	5h	6h	8h	10 h	20h
1.60V/cell	88.6	58.4	43.7	35.0	25.5	18.3	14.9	10.9	8.6	6.15	4.89	4.16	3.56	2.81	2.29	1.23
1.65V/cell	85.9	57.3	42.9	34.3	25.0	18.1	14.7	10.8	8.5	6.08	4.83	4.11	3.53	2.78	2.28	1.22
1.67V/cell	85.1	56.7	42.5	34.1	24.9	18.0	14.6	10.7	8.46	6.06	4.82	4.1	3.52	2.77	2.27	1.22
1.70V/cell	83.0	55.5	41.6	33.5	24.5	17.8	14.4	10.6	8.38	6.01	4.78	4.08	3.49	2.75	2.25	1.21
1.75V/cell	80.0	53.7	40.5	32.8	24.0	17.5	14.2	10.5	8.28	5.93	4.72	4.03	3.45	2.73	2.23	1.2
1.80V/cell	76.8	52.0	39.4	32.0	23.6	17.1	14.0	10.3	8.16	5.85	4.67	3.98	3.42	2.7	2.21	1.19
1.85V/cell	72.1	49.4	37.8	31.0	22.9	16.8	13.7	10.1	8.03	5.77	4.61	3.93	3.37	2.66	2.18	1.17




Phone (US): (775) 825-6500

Charging

Cycle Applications: Apply constant voltage charge at 2.35VPC – 2.45VPC (14.1 to 14.7 volts for 12V Monobloc) at 20°C. The initial charging current should be set at less than C/5 Amps. Switch to float charge when the current falls to a 3% capacity rate to avoid overcharging. Stand-By or "Float" Service: Apply constant voltage charge of 2.25VPC – 2.30VPC (13.5 to 13.8 volts for 12V Monobloc) at 20°C. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition. Temperature Compensation: Charging voltage for both cyclic and stand-by applications should be regulated in relation to ambient temperature. As temperature rises, charging voltage should be reduced to prevent overcharge and increased as the temperature falls to avoid undercharge. For further charging information, including temperature compensation factors, see the Power-Sonic Technical Manual.

Engineering Drawing



For Further Information

Please refer to our website, **www.power-sonic.com**, for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.

Approvals



CE marking confirms a product meets EU safety, health, and environmental protection standards for battery and energy systems.



Conflict-free mineral certification ensuring ethical sourcing and transparent supply chain for responsible production.



Extended mineral reporting meets global supply chain transparency standards for responsible and ethical sourcing practices.



IEC 60896 standard ensures stationary lead-acid batteries meet safety, performance, and float charge application requirements.



ISO 9001:2015 certification ensures consistent quality management and manufacturing standards for energy storage products.



PFAS-free certification verifying environmentally responsible manufacturing of batteries and energy storage technologies.



California Proposition 65 compliant, providing consumer safety through reduced chemical exposure in battery manufacturing.



REACH compliant with EU chemical safety standards ensuring restricted substances are controlled in all battery components.



RoHS compliance ensures restriction of hazardous substances in electrical, electronic, and battery-powered products.



Sealed lead-acid batteries classified UN2800 nonspillable, certified safe for air, sea, and ground transport worldwide.



SVHC compliant with EU REACH regulations for Substances of Very High Concern used in electrical and energy storage products.



U.S. EPA TSCA compliance ensures toxic substances are regulated for safe manufacturing of batteries and electronic components.



UL 1989 certified for valve-regulated and vented lead-acid batteries used in UPS, emergency, and backup power applications.

